

INFRARED DECOY FLARE TM-M206

APPLICATION

The infrared decoy flare TM-M206 has been used for air shielding in not coercive rocket engines work conditions of the self guide rockets on infrared irradiance. TM-M206 considers a generator of infrared radiation. The generator has been made from special infrared flare composition on base of the MTV (Magnesium - Teflon - Viton).

This Tara Aerospace and Defence Products AD Flare has been assigned with the Nato Codification System Number NSN 1370-01-048-2138.

TECHNICAL SPECIFICATIONS

Length	205 mm (8")
Body Dimensions	25 x 25 mm (1" x 1")
Rim Dimensions	27 x 27 mm
Weight	195 g
Weight of explosive substance, max	130 g
Initiation	Impulse cartridge TM-BBU-35
Bridge resistance	0.8 - 1.2 Ω
Current strength	Not less than 4.25 A
Dispensing Systems	M130, AN/ALE-40, AN/ALE-45, AN/ALE-47
UN Number	0093
ADR Number	1.3G
Packing Group	II



PACKING

Standard packing consists of 175 flares in wooden box.
Dimensions 700 x 365 x 270 mm.

Gross weight: 41.6 kg.

SHELF LIFE

Storage life: 9 years. Install life: 1 year.

